

# Reach-in Refrigerator & Freezer (No Frost)



**YPR-068S**  
**YNR-068S**



Model	(WxDxH)(mm)	Volume Ltrs	Door	Weight (KG)	Shelf	Power	Refrigerant	Comp HP	Temp °C	Unit in Container	
										20'	40'
YPR-068S	680x700x2,050	500	2 x Half SS. Door	110	4	220-240V	R134a	1/3	+2~+8 °C	21	42
YPR-135S	1,350x700x2,050	1000	4 x Half SS. Door	160	8	220-240V	R134a	1/2	+2~+8 °C	10	21
YNR-068S	680x700x2,050	500	2 x Half SS. Door	120	8	220-240V	R404a	1/3	-12~-18 °C	21	42
YNR-135S	1,350x700x2,050	1000	4 x Half SS. Door	170	8	220-240V	R404a	1/2	-12~-18 °C	10	21
YDR-135M	1,350x700x2,050	1000	2 x Glass Door & 2 SS. Door	170	8	220-240V	R134a	1/2	+2~+8 °C & -12~-18 °C	10	21



**YDR-135M**



**YPR-135S**  
**YNR-135S**



## Counter Refrigerators (No Frost)

Model	(WxDxH)(mm)	Volume Litres	Door	Weight (KG)	Shelf	Power	Refrigerant	Comp HP	Temp °C	Unit in Container	
										20'	40'
YPC-120S	1,200x700x850	250	2 x SS. Door	90	4	220-240V	R134a	1/3	+2~+8°C	22	44
YPC-120G	1,200x700x850	250	2 x Glass Door	90	4	220-240V	R134a	1/3	+2~+8°C	22	44
YPC-150S	1,500x700x850	330	2 x SS. Door	105	4	220-240V	R134a	1/3	+2~+8°C	14	28
YPC-150G	1,500x700x850	330	2 x Glass Door	105	4	220-240V	R134a	1/3	+2~+8°C	14	28
YPC-180S	1,800x700x850	440	3 x SS. Door	125	6	220-240V	R134a	1/3	+2~+8°C	14	28
YPC-180G	1,800x700x850	440	3 x Glass Door	125	6	220-240V	R134a	1/3	+2~+8°C	14	28
YPC-200S	2,000x700x850	515	3 x SS. Door	140	6	220-240V	R134a	1/3	+2~+8°C	14	28
YPC-200G	2,000x700x850	515	3 x Glass Door	140	6	220-240V	R134a	1/3	+2~+8°C	14	28



YPC-180S  
YPC-200S



YPC-150G  
YPC-120S



YPC-200G  
YPC-180G

## Counter Refrigerators with Drawers (No Frost)



YPC-180D



YPC-180E



Cake Display Cabinet

Model	(WxDxH)(mm)	Volume Litres	Door	Weight (KG)	Shelf	Power	Refrigerant	Comp HP	Temp °C	Unit in Container	
										20'	40'
YNC-120S	1,200x700x850	250	2 x SS. Door	90	4	220-240V	R404a	1/2	-12~-18°C	22	44
YNC-150S	1,500x700x850	330	2 x SS. Door	105	4	220-240V	R404a	1/2	-12~-18°C	14	28
YNC-180S	1,800x700x850	440	3 x SS. Door	125	6	220-240V	R404a	3/4	-12~-18°C	14	28
YNC-200S	2,000x700x850	515	3 x SS. Door	140	6	220-240V	R404a	3/4	-12~-18°C	14	28
YPC-150D	1,500x700x850	330	4 x 1/2 SS. Drawer	140	-	220-240V	R134a	1/3	+2~+8°C	14	28
YPC-180D	1,800x700x850	440	6 x 1/3 SS. Drawer	165	-	220-240V	R134a	1/3	+2~+8°C	14	28
YPC-150E	1,500x700x850	330	6 x 1/3 SS. Drawer	145	-	220-240V	R134a	1/3	+2~+8°C	14	28
YPC-180E	1,800x700x850	440	9 x 1/3 SS. Drawer	180	-	220-240V	R134a	1/3	+2~+8°C	14	28